

# The Gasflux Company



"THE FLUX IS

IN THE FLAME"

## OKTED

Mühendislik, Danışmanlık ve Pazarlama Ltd. Şti.

Tel : 0216 471 16 45 (pbx)

Fax : 0216 471 16 48

E-mail : oktedltd@isnet.net.tr

### LIQUID GASFLUX Type "W" a.k.a. Flameflux "E"

#### DESCRIPTION

A water-white volatile liquid. Principal ingredient  $B(OCH_3)_3$ . Will Hydrolyze in the presence of moisture, yielding boric acid. Is non-corrosive and can be handled in mild steel or copper equipment.

#### PROPERTIES

Boiling Point	52 - 56 C
Flash Point	- 8 C
Specific Gravity (20 C)	.855
Net Weight per Gallon (20 C)	7.1 Lbs.
Distillation to Dryness	Residue nil
Borate Content	4.78 - 5.12 %

#### PACKING AND SHIPPING

53 Gallon, non-returnable UN certified STC steel tighthead drums (200.6 liters)	425 Lbs.
5 Gallon, non-returnable UN certified STC steel tighthead pails	40 Lbs.

#### CLASSIFICATIONS

Flammable Liquid, n.o.s.  
(contains methyl borate, acetone and methyl alcohol)  
UN 1993  
Packing Group II  
ANSI/AWS A5.31-92 Specification: FB3-K