

The



Company

"THE FLUX IS

IN THE FLAME"

440 365-1941  
FAX 440 365-3495

32 Hawthorne Street  
P.O. Box 1170  
Elyria, Ohio 44036-1170  
www.gasfluxusa.com

## TYPE MB

### LIQUID FLAMEFLUX

#### DESCRIPTION

A water-white volatile liquid. Principal ingredient  $B(OCH_3)_3$ . Will hydrolyze in the presence of moisture, yielding boric acid. Is non-corrosive and can be handled in mild steel or copper equipment.

#### PROPERTIES

Boiling Point	58.0 – 66.8° C
Flash Point	- 5° C
Specific Gravity (20°C)	.883
Net Weight per Gallon	7.36 Lbs.
Distillation to Dryness	Residue nil
Borate Content	70 – 72 % (by weight)

#### PACKING & SHIPPING

53 Gallon (200.6 L)	non-returnable UN certified STC steel tighthead drums	435 Lbs. 197 Kg
5 Gallon (18.93 L)	non-returnable UN certified STC steel tighthead pails	42 Lbs. 19 Kg

#### CLASSIFICATIONS

Flammable Liquid, n.o.s. 3  
(contains trimethyl borate and methyl alcohol)  
UN 1993  
Packing Group II  
ANSI/AWS A5.31.92 Specification FB3-K